

# Good. Safe. Yellow.

## **AN 400**

The new Klingspor abrasive screen disc for aggressive and dust-free sanding



# Application


## Materials

- ▶ Paint/varnish/filler
- ▶ Gel coats
- ▶ Plaster, plasterboard walls
- ▶ Composite materials
- ▶ Wood, wood-based materials


## Applications

- ▶ Intermediate and finishing of paint/varnish/filler, composite materials and gel coats
- ▶ Sanding of filled joints and drywall panels
- ▶ Effective sanding of hard and soft wood-based materials


## Machines



# Product advantages



Rear side



Grain side


- ✓ **Extremely tear-resistant and flexible polyester cloth**

- ✓ **Effective and full-surface extraction thanks to open lattice structure**

- ✓ **No clogging of the disc**

# Target groups

- ▶ Carpenters/joiners
- ▶ Wood processing industry
- ▶ Drywall installations
- ▶ Automotive
- ▶ Boat construction
- ▶ Wind energy industry



# Your advantages

## Excellent process reliability

- ▶ No tearing of the disc, even under high loads
- ▶ Ideal for finish sanding and sanding of contours

## Superbly smooth sanding


- ▶ Almost dust-free operation
- ▶ Independent of existing hole systems
- ▶ Improved occupational safety thanks to reduced dust formation

## Exceptional service life

- ▶ No clogging
- ▶ No sanding marks caused by accumulation of dust particles

Abrasive screen, self-fastening

## AN 400



### Properties

Grain	Aluminium oxide
-------	-----------------

### Applications

Paint/Varnish/Filler	●	Composite materials	●
Gel coats	●	Wood	●
Plaster	●	Wood based materials	●
Plasterboard walls	●		

**Advantages:** Effective and full-surface dust extraction thanks to open lattice structure - Dust-free sanding extends the service life of the abrasive - Improved health and safety due to reduced dust formation at the work station - Independent of existing extraction hole patterns

### Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------

Width x Length in mm	Grit	Packing unit/pcs.	Cat. number	Discount group
125	80	50	337898	7
125	100	50	337899	7
125	120	50	337900	7
125	150	50	337901	7
125	180	50	337905	7
125	240	50	337904	7
125	320	50	337903	7
125	400	50	337902	7
150	80	50	337886	7
150	100	50	337887	7
150	120	50	337885	7
150	150	50	337884	7
150	180	50	337883	7
150	240	50	337888	7
150	320	50	337876	7
150	400	50	337877	7
225	80	25	337871	7
225	100	25	337875	7
225	120	25	337873	7
225	150	25	337874	7
225	180	25	337872	7
225	240	25	337878	7

Abrasive screen, self-fastening

## AN 400



### Properties

Grain	Aluminium oxide
-------	-----------------

### Applications

Paint/Varnish/Filler	●	Composite materials	●
Gel coats	●	Wood	●
Plaster	●	Wood based materials	●
Plasterboard walls	●		

**Advantages:** Effective and full-surface dust extraction thanks to open lattice structure - Dust-free sanding extends the service life of the abrasive - Improved health and safety due to reduced dust formation at the work station - Independent of existing extraction hole patterns

### Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------

Width x Length in mm	Grit	Packing unit/pcs.	Cat. number	Discount group
80 x 133	80	50	337892	7
80 x 133	100	50	337891	7
80 x 133	120	50	337890	7
80 x 133	150	50	337894	7
80 x 133	180	50	337889	7
80 x 133	240	50	337893	7
80 x 133	320	50	337895	7
80 x 133	400	50	337896	7

Klingspor Abrasives Ltd  
Dukeries Business Centre  
31-33 Retford Road  
Worksop, Notts  
S80 2PU

Tel: 01909 712 310  
Fax: 01909 712 420  
Email: [sales@klingspor.co.uk](mailto:sales@klingspor.co.uk)  
Website: [www.klingspor.co.uk](http://www.klingspor.co.uk)

